

SURFACE CLEANING NOZZLE

ORBIJET

MAINTAIN CONSISTENCY MAXIMIZE EFFICIENCY

EASY TWO-MINUTE IN-THE-FIELD OVERHAUL
Using the Rebuild Kit with two standard hex wrenches

MAGNETIC BRAKING SYSTEM

Controls rotational speed to reduce wear and maximize impact without streaking

3 TOOLS IN 1

Two nozzles for a narrow path, two for a wide path (the widest in the industry), or all four nozzles for a complete clean

TWIS-LOK™ LIGHTWEIGHT SHROUD

Protects tools and provides safe water displacement



NOZZLE SPRAY

ORBIJET WIDE

(LARGER SPRAY AREA)

ORBIJET NARROW

(HARDER HITTING)

COMPETITION



INLET CONNECTION*	SPEED RANGE	DIAMETER (LESS SHROUD)		ASSEMBLY LENGTH (WITH ADAPTER)		ASSEMBLY WEIGHT		MAX. FLOW RATE (HAND GUN)		MAX. OPERATING PRESSURE**	
	RPM	IN	MM	IN	MM	LBS	KG	GPM	LPM	PSI	BAR
3/8" NPT Female	1000-1500	2.0	51	4.0	102	2.1	0.95	7.5	28.4	22,000	1517

*Inlet connection on the tool is 9/16" MP; inlet listed is with the adapter.

**With the 15K Adapter (not shown), Orbi-Jet X22 max pressure is 15,000 psi (1034 bar).



SEE IT IN ACTION
ORBIJET™

Solutions



800.231.8192
sales@waterblast.com



www.waterblast.com



5905 Thomas Road
Houston, TX 77041