

SURFACE CLEANING NOZZLE

ORBIJET™ X22

MAINTAIN CONSISTENCY MAXIMIZE EFFICIENCY

MAGNETIC BRAKING SYSTEM

Controls rotational speed maximum cleaning and minimal wear.
NO OIL OR FRICTION BRAKE!

WATER BEARING

Self-rotating tool spins on a water bearing.
NO PHYSICAL BEARINGS NEEDED!

TWIS-LOK™ LIGHTWEIGHT SHROUD

Protects tools and provides safe water displacement

TWO-MINUTE IN-THE-FIELD OVERHAUL

Rebuild Kit provides easy in-field
repair using standard wrenches.
NO SPECIAL TOOLS REQUIRED!



NOZZLE SPRAY

ORBIJET WIDE

(LARGER SPRAY AREA)

ORBIJET NARROW

(HARDER HITTING)

COMPETITION

***NEW!** Low Flow Orbi-Jet X22 available that can reach flows as low as 2.5gpm at 20,000 PSI



| MODEL | NOZZLE PART NUMBER | INLET CONNECTION | SPEED RANGE | DIAMETER (LESS SHROUD) | | ASSEMBLY LENGTH | | ASSEMBLY WEIGHT | | MAX. FLOW RATE | | MAX. OPERATING PRESSURE | |
|----------|--------------------|------------------|-------------|------------------------|----|-----------------|----|-----------------|------|----------------|-----|-------------------------|------|
| | | | | IN | MM | IN | MM | LBS | KG | GPM | LPM | PSI | BAR |
| STANDARD | 63230 | 9/16" MP Female | RPM | | | | | | | | | | |
| LOW FLOW | 72296 | | 1000-3000 | 2.0 | 51 | 3.7 | 94 | 2.1 | 0.95 | 18 | 68 | 22K | 1500 |

*Inlet connection on the tool is 9/16 MP; inlet listed is with the adapter.



SEE IT IN ACTION
ORBIJET™



800.231.8192
sales@waterblast.com



www.waterblast.com



4133 Southerland Rd.
Houston, TX 77092